


ROOFBOND AC AirVent

Product:	ROOFBOND AC AirVent	
Supplier:	MASTERPLAST International Kft., 8143 Sárszentmihály, Árpád u. 1/a. (www.masterplastgroup.com)	
Size, packaging:	In 5 m long rolls	
Fields of application:	Used for ventilation of ridge tiles along the ridges and hips. It can be fixed onto the surface of the tiles by the adhesive strips.	
Material:	Shaped aluminium strip lacquered with polyester paint, with perforated PP fabric in the middle and two butyl strips on the reverse side, along the edges.	

Properties	Relevant standards	Technical data
Length	MDV (Manufacturer's Declared Value)	5 m/roll
Width	MDV	300 mm
Thickness of aluminium layer	MDV	0,10 - 0,12 mm
Ventilation cross section	MDV	~ 150 cm ² /m
Unit weight of PP layer	MDV	100 g/m ²
Temperature during installation	MDV	(+)5°C - (+)40°C
Resistance to temperature	MDV	(-)30°C - (+)80°C

Storage and handling

Under dry conditions, protected against atmospheric exposure, especially sun-radiation and other heat sources as well as against moisture and rain.
Temperature during storage: (+)5°C - (+)30°C.

Guarantee, warranty:

In accordance with the current legislations and the conditions of the distributor - 5 years with proper storage and installation. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims.

Health and safety

No labelling required in accordance with the relevant regulation (EC) No. 1907/2006 of the European Parliament and of the Council (REACH).

This datasheet corresponds to our current knowledge, experiences and general informations on the subject, but may be revised as new knowledge and/or experience becomes available. It does not imply any legally binding assurance. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

This technical datasheet is applied to products sold by Masterplast International Kft. and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com. Modification of the technical datasheet repeals the previously issued versions!