


Product:	ROOFBOND AC AirVent	
Supplier:	MASTERPLAST - H-8143 Sárszentmihály, Árpád u. 1/A. www.masterplastgroup.com	
Size, packaging:	5 meter long rolls	
Function, recommended field of use:	Ventilation and tightening ridge tape for pitched roofs covered with tiles. It enables the water vapour to leave the roof construction or the attic and at the same time prevents getting water and dust underneath the roof. The self-adhesive strips fix the ridge tape to the surface of the tiles.	
Material:	Steam permeable ridge tape that consists from two aluminum stripes (in black, brown or red colors) with self adhesive stripes on the bottom, joined together with a vapour-permeable nonwoven spunbond layer with perforated ventilation holes.	

Properties	Method	Technical data	
Length	Manufacturer's declared value	5	m
Width		300	mm
Thickness of aluminium stripe		0,10 - 0,12	mm
Ventilation surface		~ 210	cm ² /m
Nonwoven spunbond weight		~ 90	g/m ²
Treating temperature		(+)5 - (+)40	°C
Temperature resistance		(-)30 - (+)80	°C
Reaction to fire		B2	class

Storage and handling

Store in cold and dry place, in the intact original boxes. Storage temperature: (+)10°C - (+)40°C. Can be used for 12 months after production date.

Guarantee, warranty

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims.

Health and safety

No labelling required in accordance with the relevant regulation (EC) No. 1907/2006 of the European Parliament and of the Council.

This datasheet corresponds to our current knowledge, experiences and general informations on the subject, but may be revised as new knowledge and/or experience becomes available. It does not imply any legally binding assurance. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures. The manufacturer supposes essential technical skill and skillfull application during construction.

This technical datasheet is applied to products sold by Masterplast Group and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastinternational.com. Herewith the previously issued versions of this datasheets lose their validity and must be replaced by this version!

TD_Roofbond.AC.Airvent-20241205_EN

*Issued: 2024. 12. 05.